




TECHNICAL SHEET



Standard Aluminum Profile



LED Type:	70pcs 2835leds/m
Rated Power:	6W/m
Input Voltage:	24V DC
CCT:	2700K、3000K、4000K、5000K、6500K、 Red、 Green、 Blue、 Yellow
CRI:	>80 / >90 option
Beam Angle:	120°
FPCB Width:	8mm, White Color
FPCB Thickness:	2Oz, Double layer
Working Temperature:	-20°C~+50°C
Storage Temperature:	-20°C~+60°C
Life Span:	50,000+ Hours
IP Grade:	IP20 / IP65 / IP67 / IP68



Brand/Model	LED Strip -24V-6W-CRI90
Country of Origin	P.R.C
Description	High quality 2835 LED Strip with power consumption of 6w per meter. 120lm per w at 720lm. Comes high color rendering index of 90. color temperature of 2700K,3000K,4000K & 6500K available to provide for the ambient required. IP20, IP65 , IP67 and IP68 allows for different type of applications. With Remote Group IP65 24V Converters LED Driver. (10m Max to one driver).Every 7leds as a unit can be cut, to reach high lumen efficacy;
Materials	Flexible LED Strip
Compliance	CE
Protection Classification	IP67
Lamp	San'AN SELS-2835 SMD LED Lumen: >720lm CRI: >90 Colour Temperature: 3000K (Warm White) Lifespan: 50,000hours Beam angle:120D Luminaire Efficacy: 120lm/w
Control Gear	Remote Group IP65 No-Dimmable LED Driver
Mounting Method	Surface Mounted
Dimension	1000 x 10 x 4.2mm(Length X Width X Height)